

# CNS 300 Trend

CONVECTORS

PRODUCT-NO.: 236530

Even in small or cramped rooms, you shouldn't have to miss out on cosy warmth. That's why this heater is so compact. With a depth of just 10 cm, it is particularly slimline, requiring very little space for installation. Nevertheless, the appliance offers you excellent thermal comfort.



Although the wall mounted convector blends very discreetly into your room, it supplies heat efficiently. Useful features contribute to its efficiency: the weekly timer and open window detection make operation easier for you.

## The main features

Wall mounted convector – ideal as a supplementary heater or interim heater in spring/autumn

---

Even, quiet, air heating

---

Metal casing and slimline design

---

Operating controls with illuminated LCD screen

---

Weekly timer, frost protection and open window detection

---

Control unit with self-learning capability: automatic calculation of the preheat time in timer mode

---

ON/OFF switch and overheating protection



Type	CNS 100 Trend	CNS 150 Trend	CNS 200 Trend
Part no.	236526	236527	236528

## Heating output

Rated heating output P <sub>nom</sub>	1.00 kW	1.50 kW	2.00 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	1.00 kW	1.50 kW	2.00 kW

## Auxiliary power consumption

H rated heating output e <sub>lmax</sub>	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e <sub>lmin</sub>	0.00 kW	0.00 kW	0.00 kW
Dby mode e <sub>lSB</sub>	0.00 kW	0.00 kW	0.00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	x	x	x

## Other control options

Room temperature control, with presence detection	-	-	-
Room temperature control, with open window detection	x	x	x
With distance control option	-	-	-
With adaptive start control	x	x	x
With working time limitation	-	-	-
With black bulb sensor	-	-	-



Type	CNS 250 Trend	CNS 300 Trend
Part no.	236529	236530

## Heating output

Rated heating output P <sub>nom</sub>	2.50 kW	3.00 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	2.50 kW	3.00 kW

## Auxiliary power consumption

H rated heating output e <sub>Hmax</sub>	0.00 kW	0.00 kW
H minimum heating output e <sub>Hmin</sub>	0.00 kW	0.00 kW
Dby mode e <sub>LSB</sub>	0.00 kW	0.00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-
Two or more manual stages, no room temperature control	-	-
With mechanic thermostat room temperature control	-	-
With electronic room temperature control	-	-
Electronic room temperature control plus day timer	-	-
Electronic room temperature control plus week timer	x	x

## Other control options

Room temperature control, with presence detection	-	-
Room temperature control, with open window detection	x	x
With distance control option	-	-
With adaptive start control	x	x
With working time limitation	-	-
With black bulb sensor	-	-

Depth including wall mounting bracket

## **Contact information**

You have questions? We appreciate to help you:

SALES HOTLINE

**+91 2067 48 0928**

SERVICE HOTLINE

**+91 2067 48 0909**

Write an email to [sales@stiebel-eltron.in](mailto:sales@stiebel-eltron.in)

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.