

MHP 65 E

NATURAL STONE HEATERS

PRODUCT-NO.: 233661

Natural stone heaters: Cosy warmth delivered with individual charm.

These natural stone panels not only look stunning, they also give out a very pleasant heat. Thanks to a range of different designs, the natural stone heaters fit perfectly into a wide variety of interior design concepts.

Every model absolutely natural.

As every panel is made from natural stone into which only a thin cable is embedded, every heater is unique in colour and structure. Consequently, a natural stone heater lends any bathroom and living room a very special and individual kind of charm.



The main features

PRINOS natural stone heater

Dolomite marble

650 W heating output

Ideal as supplementary or booster heater

Pleasant radiated heat

Portrait or landscape installation is possible



Type	MHP 35 E	MHP 65 E	MHP 85 E
Part no.	233660	233661	233662

Heating output

Rated heating output P_{nom}	0,4 kW	0,7 kW	0,9 kW
Minimum heat output (standard value) P_{min}	0,0 kW	0,0 kW	0,0 kW
Maximum continuous heating output $P_{max,c}$	0,4 kW	0,7 kW	0,9 kW

Auxiliary power consumption

D heating output $e_{l_{max}}$	0,000 kW	0,000 kW	0,000 kW
Heat output $e_{l_{min}}$	0,000 kW	0,000 kW	0,000 kW
Dby mode $e_{l_{SB}}$	0,000 kW	0,000 kW	0,000 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manually adjustable stages, no room temperature control	-	-	-
Room temperature control with mechanical thermostat	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control and time of day control	-	-	-
Electronic room temperature control and day of week control	x	x	x

Other control options

Room temperature control with occupancy detection	-	-	-
Room temperature control with open window detection	-	-	-
With remote control option	-	-	-
With adaptive control for start of heating	x	x	x
With restricted operating times	-	-	-
With black bulb sensor	-	-	-



Type	MHP 115 E	MHP 145 E	MHP 165 E
Part no.	233663	233664	233665

Heating output

Rated heating output P_{nom}	1,2 kW	1,5 kW	1,7 kW
Minimum heat output (standard value) P_{min}	0,0 kW	0,0 kW	0,0 kW
Maximum continuous heating output $P_{max,c}$	1,2 kW	1,5 kW	1,7 kW

Auxiliary power consumption

D heating output $e_{l_{max}}$	0,000 kW	0,000 kW	0,000 kW
Heat output $e_{l_{min}}$	0,000 kW	0,000 kW	0,000 kW
Dby mode $e_{l_{SB}}$	0,000 kW	0,000 kW	0,000 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manually adjustable stages, no room temperature control	-	-	-
Room temperature control with mechanical thermostat	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control and time of day control	-	-	-
Electronic room temperature control and day of week control	x	x	x

Other control options

Room temperature control with occupancy detection	-	-	-
Room temperature control with open window detection	-	-	-
With remote control option	-	-	-
With adaptive control for start of heating	x	x	x
With restricted operating times	-	-	-
With black bulb sensor	-	-	-

These appliances may only be installed and commissioned in conjunction with external room temperature controllers that have the following functions: Electronic room temperature control with day of week control and adaptive control of the start of heating. These requirements are met by the STIEBEL ELTRON RTU-TC, RTU-S UP Stiebel® and SRC C digital room temperature controllers. Failure to observe these requirements will result in the loss of the CE designation.

Contact information

You have questions? We appreciate to help you:

SALES HOTLINE

+91 2067 48 0928

SERVICE HOTLINE

+91 2067 48 0921

Write an email to sales@stiebel-eltron.in

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.