

RHB 700

RADIANT HEATER

PRODUCT-NO.: 234424

The frameless and very slim design with the minimalist glass surface fits into any modern environment. Our radiant heaters emit a special form of heat which is perceived as particularly pleasant. The all-round bezel on the back means that the wall mounting bracket and power supply are no longer visible post installation.



The main features

700 W heating output

Black glass surface

Pleasant radiated heat

The clear design language highlights high grade interior appeal

Ideal for use as a booster or auxiliary heater

Optional installation vertically and horizontally

Straightforward and quick installation by a single person



Type	RHB 300	RHB 500	RHB 700
Part no.	234422	234423	234424
Connected load	0,280 kW	0,47 kW	0,66 kW
Width	600 mm	1000 mm	1400 mm
Depth	49 mm	49 mm	49 mm
Height	600 mm	600 mm	600 mm

Technical data



Type	RHB 900
Part no.	234425
Connected load	0,85 kW
Width	1800 mm
Depth	49 mm
Height	600 mm

Technical data

These appliances may only be installed and commissioned in conjunction with external room temperature controllers that have the following functions: Electronic room temperature control with day of week control and adaptive control of the start of heating. These requirements are met by the STIEBEL ELTRON RTU-TC, RTU-S UP Stiebel® and SRC C digital room temperature controllers. Failure to observe these requirements will result in the loss of the CE designation.

Contact information

You have questions? We appreciate to help you:

SALES HOTLINE

+91 2067 48 0928

SERVICE HOTLINE

+91 2067 48 0921

Write an email to sales@stiebel-eltron.in

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.