

RHW 500

RADIANT HEATER

PRODUCT-NO.: 234427

The frameless and very slim design with the minimalist glass surface fits into any modern environment. Our radiant heaters emit a special form of heat which is perceived as particularly pleasant. The all-round bezel on the back means that the wall mounting bracket and power supply are no longer visible post installation.



The main features

500 W heating output

White glass surface

Pleasant radiated heat

The clear design language highlights high grade interior appeal

Ideal for use as a booster or auxiliary heater

Optional installation vertically and horizontally

Straightforward and quick installation by a single person



Type	RHW 300	RHW 500	RHW 700
Part no.	234426	234427	234428

Heating output

Rated heating output P_{nom}	0,3 kW	0,5 kW	0,7 kW
Minimum heat output (standard value) P_{min}	0,0 kW	0,0 kW	0,0 kW
Maximum continuous heating output $P_{max,c}$	0,3 kW	0,5 kW	0,7 kW

Auxiliary power consumption


D heating output $e_{l_{max}}$	0,000 kW	0,000 kW	0,000 kW
Heat output $e_{l_{min}}$	0,000 kW	0,000 kW	0,000 kW
Dby mode $e_{l_{SB}}$	0,000 kW	0,000 kW	0,000 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manually adjustable stages, no room temperature control	-	-	-
Room temperature control with mechanical thermostat	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control and time of day control	-	-	-
Electronic room temperature control and day of week control	x	x	x

Other control options

Room temperature control with occupancy detection	-	-	-
Room temperature control with open window detection	-	-	-
With remote control option	-	-	-
With adaptive control for start of heating	x	x	x
With restricted operating times	-	-	-
With black bulb sensor	-	-	-



Type	RHW 900
Part no.	234429

Heating output

Rated heating output P_{nom}	0,9 kW
Minimum heat output (standard value) P_{min}	0,0 kW
Maximum continuous heating output $P_{max,c}$	0,9 kW

Auxiliary power consumption

D heating output $e_{l_{max}}$	0,000 kW
Heat output $e_{l_{min}}$	0,000 kW
Dby mode $e_{l_{SB}}$	0,000 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manually adjustable stages, no room temperature control	-
Room temperature control with mechanical thermostat	-
With electronic room temperature control	-
Electronic room temperature control and time of day control	-
Electronic room temperature control and day of week control	x

Other control options

Room temperature control with occupancy detection	-
Room temperature control with open window detection	-
With remote control option	-
With adaptive control for start of heating	x
With restricted operating times	-
With black bulb sensor	-

These appliances may only be installed and commissioned in conjunction with external room temperature controllers that have the following functions: Electronic room temperature control with day of week control and adaptive control of the start of heating. These requirements are met by the STIEBEL ELTRON RTU-TC, RTU-S UP Stiebel® and SRC C digital room temperature controllers. Failure to observe these requirements will result in the loss of the CE designation.

Contact information

You have questions? We appreciate to help you:

SALES HOTLINE

+91 2067 48 0928

SERVICE HOTLINE

+91 2067 48 0921

Write an email to sales@stiebel-eltron.in

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.