

FTT 960 C

UNDERFLOOR HEATING

PRODUCT-NO.: 234294

Enjoy warmth to the tips of your toes

With our electric underfloor heating, you never need to have cold feet in the bathroom again. Your very first steps in the morning will take you across warm floor tiles. This will get your day off to a great start.

Working in tandem

Your installer will simply lay the heating mat under the tiled floor. It is easy to install - not only in new builds, but also in modernisation projects. The mats are also suitable for floor-level showers. If you combine the heating mats with warm water underfloor heating, you'll be covered all year round. Your central heating will keep the floor nice and warm in the winter and the mat will do the job in the spring and autumn.

The main features

Ideal for the bathroom

Even temperature distribution across the floor

Independent of the existing heating system

Suitable for new build, renovation and modernisation thanks to low installed height

With stepless temperature adjustment

Additional temperature controller required

Basis heating mat for the temperate heating of ceramic floor coverings

Turbo heating mat for better temperate heating with thick tiles or natural stone floors

**FTT 160 C**

Product-No.: 234287

**FTT 240 C**

Product-No.: 234288

**FTT 320 C**

Product-No.: 234289

**FTT 400 C**

Product-No.: 234290

**FTT 480 C**

Product-No.: 234291

**FTT 640 C**

Product-No.: 234292

**FTT 800 C**

Product-No.: 234293



FTT 1120 C

Product-No.: 234295



Type	FTT 160 C	FTT 240 C	FTT 320 C
Part no.	234287	234288	234289

Technical data

Power supply	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Connected load	160 W	240 W	320 W
Area-specific output	160 W/m ²	160 W/m ²	160 W/m ²
Heat conductor load	11 W/m	11 W/m	11 W/m
IP rating	IP X7	IP X7	IP X7
Surface area	1.00 m ²	1.50 m ²	2.00 m ²
Length	2 m	3 m	4 m
Strength	3 mm	3 mm	3 mm
Width	500 mm	500 mm	500 mm



Type	FTT 400 C	FTT 480 C	FTT 640 C
Part no.	234290	234291	234292

Technical data

Power supply	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Connected load	400 W	480 W	640 W
Area-specific output	160 W/m ²	160 W/m ²	160 W/m ²
Heat conductor load	11 W/m	11 W/m	11 W/m
IP rating	IP X7	IP X7	IP X7
Surface area	2.50 m ²	3.00 m ²	4.00 m ²
Length	5 m	6 m	8 m
Strength	3 mm	3 mm	3 mm
Width	500 mm	500 mm	500 mm



Type	FTT 800 C	FTT 960 C	FTT 1120 C
Part no.	234293	234294	234295

Technical data

Power supply	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Connected load	800 W	960 W	1120 W
Area-specific output	160 W/m ²	160 W/m ²	160 W/m ²
Heat conductor load	11 W/m	11 W/m	11 W/m
IP rating	IP X7	IP X7	IP X7
Surface area	5.00 m ²	6.00 m ²	7.00 m ²
Length	10 m	12 m	14 m
Strength	3 mm	3 mm	3 mm
Width	500 mm	500 mm	500 mm

Contact information

You have questions? We appreciate to help you:

SALES HOTLINE

+91 2067 48 0928

SERVICE HOTLINE

+91 2067 48 0921

Write an email to sales@stiebel-eltron.in

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.