

DCE-X 10/12 Premium

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238159

Enjoy hot water on demand at any time Call up precise information at any time **Make way for efficiency** First thing in the morning, throughout the day or late at night: water is always available at the right temperature, whenever you need it. That's the assurance and precision you get with this compact instantaneous water heater. This is made possible by the memory function: two buttons, which you can use to quickly and easily save frequently used temperatures.



The main features

Fully electronically controlled compact instantaneous water heater

Maximum energy efficiency and accurate temperature delivery at all times thanks to 4i technology

Easy operation via large, illuminated multifunction display

Power saving mode due to optional ECO function

High grade design

Two temperature memory buttons for quick temperature selection

Temperature limit can be fixed at 43 °C, 50 °C or 55 °C

Exceptionally slimline, compact design



DCE-X 6/8 Premium

Product-No.: 238158



Type	DCE-X 6/8 Premium	DCE-X 10/12 Premium
Part no.	238158	238159

Technical data

Rated voltage	220 V	220 V
Rated voltage 1	220 V	220 V
Rated voltage 2	230 V	230 V
Rated voltage 3	240 V	240 V
Rated output	6.0/8.0 kW	10.0/12.0 kW
Rated output 1	6.0/8.0 kW	10.0/12.0 kW
Rated output 2	6.6/8.7 kW	11.0/13.1 kW
Rated output 3	7.2/9.6 kW	12.0/14.3 kW
Rated current	27.3/36.4 A	45.5/54.5 A
Rated current 1	27.3/36.4 A	45.5/54.5 A
Rated current 2	28.5/38.0 A	47.8/57.0 A
Rated current 3	30.0/40.0 A	50.0/59.5 A
Fuse protection	30/40 A	50/60 A
Fuse protection 1	30/40 A	50/60 A
Fuse protection 2	30/40 A	50/60 A
Fuse protection 3	30/40 A	50/60 A
Frequency	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz
Frequency 3	50/60 Hz	50/60 Hz

Phases	1/N/PE	1/N/PE
Conductivity $\sigma_{15} \leq$	910 $\mu\text{S}/\text{cm}$	910 $\mu\text{S}/\text{cm}$
Resistivity $\rho_{15} \geq$	1100 $\Omega \text{ cm}$	1100 $\Omega \text{ cm}$
IP rating	IP25	IP25
Temperature setting	Ki, 20–60 °C	Ki, 20–60 °C
Colour	white	white
Switch-on water flow rate	1.3 l/min	1.3 l/min
Height	372 mm	372 mm
Width	217 mm	217 mm
Depth	109 mm	109 mm
Weight	2.50 kg	2.50 kg

Contact information

You have questions? We appreciate to help you:

SALES HOTLINE

+91 2067 48 0928

SERVICE HOTLINE

+91 2067 48 0909

Write an email to **sales@stiebel-eltron.in**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.