DHE 27 COMFORT INSTANTANEOUS WATER HEATERS

Use water your way

Every one of our fully electronic instantaneous water heater models provides hot water at the exact temperature you have set at all times. No ifs or buts. The 4i technology ensures that nothing interferes with the outlet temperature. Enjoy constant hot water in the shower, even if somebody needs to wash their hands at the washbasin beside you.

Make all your own choices

The haptic rotary selector ensures the appliance is very easy to operate: intuitive, instant, precise.

Know exactly what's going on

The illuminated multifunction display gives you a clear overview of your required water temperature, the ECO level and current power consumption. You can check energy consumption, flow rate, time, status and service information in the lower part of the display.

The main features

Instantaneous water heater with full electronic control


Accurate water temperature delivery at all times thanks to 4i technology

Sufficient hot water for multiple draw-off points

Easy to use backlit multifunction display

Energy and water consumption LEDs

Particularly economical operation with ECO mode



PRODUCT-NO.: 202657




DHE 18/21/24 Product-No.: 202656



Individual memory buttons for setting preferred temperatures

Additional functions such as a temperature limit, wellness shower program, automated bath filling and childproofing for greater convenience and safety



Technical data

Rated voltage	400 V	400 V
Rated voltage 1	380 V	380 V
Rated voltage 2	400 V	400 V
Rated output	18/21/24 kW	27 kW
Rated output 1	16,2/19/21,7 kW	24,4 kW
Rated output 2	18/21/24 kW	27 kW
Rated current	29/31/35 A	39 A
Rated current 1	27,6/29,5/33,3 A	37,1 A
Rated current 2	29/31/35 A	39 A
Fuse protection	32/32/35 A	40 A
Fuse protection 1	32/32/35 A	40 A
Fuse protection 2	32/32/35 A	40 A
Frequency	50/60 Hz	50/- Hz
Frequency 1	50/60 Hz	50/- Hz
Frequency 2	50/60 Hz	50/- Hz
Phases	3/PE	3/PE
Conductivity σ15 ≤	1111 µS/cm	1111 µS/cm
Resistivity ρ15 ≥	900 Ω cm	900 Ω cm
IP rating	IP25	IP25
Temperature setting	20-60 °C	20-60 °C
Colour	white	white

Switch-on water flow rate	>2,5 l/min	>2,55 l/min
Height	466 mm	466 mm
Width	225 mm	225 mm
Depth	116 mm	116 mm
Weight	3.10 kg	3.10 kg

Contact information

You have questions? We appreciate to help you: SALES HOTLINE +91 2067 48 0928 SERVICE HOTLINE +91 2067 48 0909

Write an email to sales@stiebel-eltron.in

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.