

# DHC 8 EC (STE)

MINI INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 235092

## The main features

Microprocessor control with inlet and outlet temperature sensor for accurate temperature delivery

Selection of temperature (40, 50, 60 °C) up to maximum output for maximum convenience

Manually adjustable flow limiter in cold water inlet (can be adjusted by the contractor) for greater energy savings

LED ON indicator on the appliance cover provides clear information about appliance status

Installation on finished & unfinished walls is possible

Integrated high limit safety cut-out and RCD for maximum safety

IP 25 for greater protection against water ingress (hoseproof)

Tubular heater made of copper for a longer service life





Type	DHC 6 EC (STE)	DHC 8 EC (STE)
Part no.	235091	235092

## Technical data

Rated voltage 1	220 V	220 V
Rated voltage 2	230 V	230 V
Rated voltage 3	240 V	240 V
Rated output 1	6,0 kW	8,0 kW
Rated output 2	6,6 kW	8,7 kW
Rated output 3	7,1 kW	9,5 kW
Rated current 1	27,3 A	36,4 A
Rated current 2	28,7 A	37,8 A
Rated current 3	29,6 A	39,6 A
Fuse 1	32 A	40 A
Fuse 2	32 A	40 A
Fuse 3	32 A	40 A
Phases	1/N/PE ~220-240V	1/N/PE ~220-240V
Type	sealed	sealed
Max. permissible pressure	1 MPa	1 MPa
Minimum supply pressure	0,02 MPa	0,02 MPa
Colour	grey	grey
Weight	2 kg	2 kg

## **Contact information**

You have questions? We appreciate to help you:

SALES HOTLINE

**+91 2067 48 0928**

SERVICE HOTLINE

**+91 2067 48 0921**

Write an email to [sales@stiebel-eltron.in](mailto:sales@stiebel-eltron.in)

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.